
PROGRESS[®] ORBIX[®]

Release Notes

Version 3.3, Service Pack 11, March 2012

Progress Orbix v3.3.11

© 2012 Progress Software Corporation and/or its subsidiaries or affiliates. All rights reserved.

These materials and all Progress® software products are copyrighted and all rights are reserved by Progress Software Corporation. The information in these materials is subject to change without notice, and Progress Software Corporation assumes no responsibility for any errors that may appear therein. The references in these materials to specific platforms supported are subject to change.

Actional, Apama, Artix, Business Empowerment, Business Making Progress, Corticon, Corticon (and design), DataDirect (and design), DataDirect Connect, DataDirect Connect64, DataDirect Technologies, DataDirect XML Converters, DataDirect XQuery, DataXtend, Dynamic Routing Architecture, Empowerment Center, Fathom, Fuse Mediation Router, Fuse Message Broker, Fuse Services Framework, IONA, Making Software Work Together, Mindreef, ObjectStore, OpenEdge, Orbix, PeerDirect, Powered by Progress, PowerTier, Progress, Progress DataXtend, Progress Dynamics, Progress Business Empowerment, Progress Empowerment Center, Progress Empowerment Program, Progress OpenEdge, Progress Profiles, Progress Results, Progress Software Business Making Progress, Progress Software Developers Network, Progress Sonic, ProVision, PS Select, RulesCloud, RulesWorld, Savvion, SequeLink, Shadow, SOAPscope, SOAPStation, Sonic, Sonic ESB, SonicMQ, Sonic Orchestration Server, SpeedScript, Stylus Studio, Technical Empowerment, WebSpeed, Xcalia (and design), and Your Software, Our Technology—Experience the Connection are registered trademarks of Progress Software Corporation or one of its affiliates or subsidiaries in the U.S. and/or other countries. AccelEvent, Apama Dashboard Studio, Apama Event Manager, Apama Event Modeler, Apama Event Store, Apama Risk Firewall, AppsAlive, AppServer, ASPen, ASP-in-a-Box, BusinessEdge, Cache-Forward, CloudEdge, DataDirect Spy, DataDirect SupportLink, Fuse, FuseSource, Future Proof, GVAC, High Performance Integration, ObjectStore Inspector, ObjectStore Performance Expert, OpenAccess, Orbacus, Pantero, POSSE, ProDataSet, Progress Arcade, Progress CloudEdge, Progress Cloudware, Progress Control Tower, Progress ESP Event Manager, Progress ESP Event Modeler, Progress Event Engine, Progress RFID, Progress RPM, Progress Responsive Cloud, Progress Responsive Process Management, Progress Software, PSE Pro, SectorAlliance, SeeThinkAct, Shadow z/Services, Shadow z/Direct, Shadow z/Events, Shadow z/Presentation, Shadow Studio, SmartBrowser, SmartComponent, SmartDataBrowser, SmartDataObjects, SmartDataView, SmartDialog, SmartFolder, SmartFrame, SmartObjects, SmartPanel, SmartQuery, SmartViewer, SmartWindow, Sonic Business Integration Suite, Sonic Process Manager, Sonic Collaboration Server, Sonic Continuous Availability Architecture, Sonic Database Service, Sonic Workbench, Sonic XML Server, The Brains Behind BAM, WebClient, and Who Makes Progress are trademarks or service marks of Progress Software Corporation and/or its subsidiaries or affiliates in the U.S. and other countries. Java is a registered trademark of Oracle and/or its affiliates. Any other marks contained herein may be trademarks of their respective owners.

Third Party Acknowledgements: One or more products in the Progress Orbix v3.3.11 release includes third party components covered by licenses that require that the following documentation notices be provided:

Progress Orbix v3.3.11 incorporates OpenSSL/SSLey v0.9.8.i technology from OpenSSL.org. Such Technology is subject to the following terms and conditions: LICENSE ISSUES

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLey license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact openssl-core@openssl.org.

OpenSSL License

Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)"
4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact openssl-core@openssl.org.
5. Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.

6. Redistributions of any form whatsoever must retain the following acknowledgment:

"This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit

(<http://www.openssl.org/>)"

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

=====

This product includes cryptographic software written by Eric Young (eay@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com).

Original SSLey License

Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com) All rights reserved. This package is an SSL implementation written by Eric Young (eay@cryptsoft.com). The implementation was written so as to conform with Netscapes SSL.

This library is free for commercial and non-commercial use as long as the following conditions are adhered to. The following conditions apply to all code found in this distribution, be it the RC4, RSA, lhash, DES, etc., code; not just the SSL code. The SSL documentation included with this distribution is covered by the same copyright terms except that the holder is Tim Hudson (tjh@cryptsoft.com).

Copyright remains Eric Young's, and as such any Copyright notices in the code are not to be removed. If this package is used in a product, Eric Young should be given attribution as the author of the parts of the library used. This can be in the form of a textual message at program startup or in documentation (online or textual) provided with the package. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement: "This product includes cryptographic software written by Eric Young (eay@cryptsoft.com)"

The word 'cryptographic' can be left out if the routines from the library being used are not cryptographic related :-).

4. If you include any Windows specific code (or a derivative thereof) from the apps directory (application code) you must include an acknowledgement:

"This product includes software written by Tim Hudson (tjh@cryptsoft.com)"

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The licence and distribution terms for any publically available version or derivative of this code cannot be changed. i.e. this code cannot simply be copied and put under another distribution licence [including the GNU Public Licence.]

Progress Orbix v3.3.11 incorporates mcpp v2.6.4 from SourceForge (<http://sourceforge.net/softwaremap/index.php>). Such technology is subject to the following terms and conditions: Copyright (c) 1998, 2002-2007 Kiyoshi Matsui kmatsui@t3.rim.or.jp All rights reserved. This software including the files in this directory is provided under the following license. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. THIS SOFTWARE IS PROVIDED BY THE AUTHOR "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Progress Orbix v3.3.11 incorporates IDL Compiler Front End v1.0 from Sun Microsystems. Such technology is subject to the following terms and conditions: COPYRIGHT NOTICE on OMG IDL CFE: Copyright 1992 Sun Microsystems, Inc. Printed in the United States of America. All Rights Reserved. This product is protected by copyright and distributed under the following license restricting its use. The Interface Definition Language Compiler Front End (CFE) is made available for your use provided that you include this license and copyright notice on all media and documentation and the software program in which this product is incorporated in whole or part. You may copy and extend functionality (but may not remove functionality) of the Interface Definition Language CFE without charge, but you are not authorized to license or distribute it to anyone else except as part of a product or program developed by you or with the express written consent of Sun Microsystems, Inc. ("Sun"). The names of Sun Microsystems, Inc. and any of its subsidiaries or affiliates may not be used in advertising or publicity pertaining to distribution of Interface Definition Language CFE as permitted herein. This license is effective until terminated by Sun for failure to comply with this license. Upon termination, you shall destroy or return all code and documentation for the Interface Definition Language CFE. The Interface Definition Language CFE may not be exported outside the United States without first obtaining the appropriate government approvals. INTERFACE DEFINITION LANGUAGE CFE IS PROVIDED AS IS WITH NO WARRANTIES OF ANY KIND INCLUDING THE WARRANTIES OF DESIGN, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE OR TRADE PRACTICE. INTERFACE DEFINITION LANGUAGE CFE IS PROVIDED WITH NO SUPPORT AND WITHOUT ANY OBLIGATION ON THE PART OF Sun OR ANY OF ITS SUBSIDIARIES OR AFFILIATES TO ASSIST IN ITS USE, CORRECTION, MODIFICATION OR ENHANCEMENT. SUN OR ANY OF ITS SUBSIDIARIES OR AFFILIATES SHALL HAVE NO LIABILITY WITH RESPECT TO THE INFRINGEMENT OF COPYRIGHTS, TRADE SECRETS OR ANY PATENTS BY INTERFACE DEFINITION LANGUAGE CFE OR ANY PART THEREOF. IN NO EVENT WILL SUN OR ANY OF ITS SUBSIDIARIES OR AFFILIATES BE LIABLE FOR ANY LOST REVENUE OR PROFITS OR OTHER SPECIAL, INDIRECT AND CONSEQUENTIAL DAMAGES, EVEN IF SUN HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 and FAR 52.227-19. Sun, Sun Microsystems and the Sun logo are trademarks or registered trademarks of Sun Microsystems, Inc. SunSoft, Inc. 2550 Garcia Avenue Mountain View, California 94043

Contents

Introduction	7
Orbix 3.3 SP 11 C++ Edition	11
Orbix 3.3 SP 11 Java Edition	13
OrbixNames 3.3 SP 11	15
Orbix Code Generation Toolkit 3.3 SP 11	17
OrbixCOMet Desktop 3.3 SP 11	19
Orbix Wonderwall 3.3 SP 11	21
OrbixEvents 3.3 SP 11	23
Orbix SSL C++ 3.3 SP 11	25
Orbix SSL Java 3.3 SP 11	27
OrbixOTS 3.3 SP 11	29
Appendix	31

Introduction

Orbix 3.3 SP 11 is a service pack release of Orbix 3.3 on the following platforms:

- Sun Solaris 9 (SPARC)
- Sun Solaris 10 (SPARC)
- HP-UX 11i (11.11) PA-RISC
- HP-UX 11i v2 (11.23) Itanium

This document contains information about Orbix 3.3 SP 11, including build information, details of bugs that are fixed in this release, known problems and workarounds, new features, tips, and deprecated features.

Orbix 3.3 SP 11 and Orbix 3.0.1

For details of the changes that took place between Orbix 3.0.1 and Orbix 3.3, see the Orbix 3.3 Release Notes at <http://communities.progress.com/pcom/docs/DOC-105220>.

Migrating from an Earlier Version of Orbix

For information on migrating from an earlier version of Orbix to Orbix 3.3 SP 11, see the migration guide at: <http://www.progress.com/en/orbix/index.html>.

Interoperability with Other Products

The Java and C++ editions of Orbix 3.3 SP 11 are tested and are interoperable with each other except for those areas that are documented under known problems.

The Java and C++ editions of Orbix 3.3 SP 11 have also been tested and are interoperable with the following Orbix products:

- Previous Orbix 3.3 C++ and Java editions
- Orbix E2A Application Server Platform 6.0 SP3 C++ and Java
- Orbix Trader 1.2.1 Java edition (no C++ edition available)
- Orbacus 4.0.5
- Orbix 3.0.1
- OrbixWeb 3.2

Licensing

- The IDL compilers, `idl.exe` and `idlj.exe`, are licensed.
- The Orbix daemon `orbixd` is licensed.
- The OrbixSSL `update` utility is licensed.
- The OrbixEvents `es` utility is licensed.
- OrbixOTS shared libraries: `libEncinaClientOrbix` and `libEncinaServerOrbix` are licensed.

Deprecated Features Policy

When a feature is deprecated it means that:

- No support for this feature is given for the current version and for subsequent versions. There are no instructions on how to use this feature, and no bugs in this feature are fixed.
- If you have not used this feature before, DO NOT start using it with this release.
- If you are already using this feature then you should remove it if at all possible.
- The feature may not be present in future versions of the product.

Documentation Errata

The following is a list of errors in the Orbix 3.3 documentation:

- The `CORBA::ORB::connectionTimeout()` is in milliseconds, and not in seconds, as stated in the *Orbix Programmer's Reference, C++ Edition*.

Development Environments

For details of the operating system versions and compiler versions on which Orbix 3.3 SP 11 is built and certified, see the following link:

<http://communities.progress.com/pcom/docs/DOC-105810>

Note: You can build and run an Orbix 3.3 SP 11 application on any of the platforms listed for Orbix 3.3 in the preceding link.

Java-Specific Information

The following subsections contain information that is relevant for all elements and services that use Java.

JRE not included

The Orbix 3.3 SP 11 installer does not include a Java Runtime Environment (JRE).

JAVA_P_FLAG

The `JAVA_P_FLAG` environment variable was introduced in Orbix 3.3 SP 7. The purpose of this flag is to enable Orbix 3.3's Java ORB class implementation to take precedence over Sun's, when running Orbix 3.3 Java applications. The Orbix 3.3 SP 11 installer automatically sets the value of this variable to `/p`.

When Orbix 3.3 SP 11 is installed, this variable is available in the `setenv.sh` environment script, which enables it to be set in the Orbix environment.

For more details, read the following Knowledge Base article (4799.578):

- [What is JAVA_P_FLAG for and how is it used in Orbix 3](#)

Orbix 3.3 SP 11 C++ Edition

This section describes changes made to the Orbix 3.3 SP 10 C++ Edition for the Orbix 3.3 SP 11 C++ Edition.

New Features

Orbix 3.3 SP 11 C++ Edition is binary compatible with Orbix 3.3 C++ Edition. Orbix 3.3 SP 11 C++ Edition now supports integration with Actional. This enables Orbix 3.3 applications and services to be monitored using Actional SOA management tools. Actional integration feature provides end-to-end visibility into the availability and performance of distributed Orbix applications. For more details, refer to the "Actional Integration with Orbix" guide for Orbix 3.3 SP11.

New and Modified APIs

Orbix 3.3 SP 11 C++ Edition is binary compatible with Orbix 3.3 C++ Edition. There are no new APIs, and no existing APIs are modified.

Functionality Removed

Orbix 3.3 SP 11 C++ Edition is binary compatible with Orbix 3.3 C++ Edition. No functionality is removed.

Deprecated Features

The following is a list of deprecated features in Orbix C++ Edition:

Feature	Description	Feature Removed	When Deprecated
<code>_bind()</code>	Should use other means	No	Orbix 3.0
Transformers	Can use SSL for security	No	Orbix 3.0
Piggy backing data with filters	Should use Service Contexts	No	Orbix 3.0
Opaque data type		No	Orbix 3.0
Orbix network protocol (POOP)	Must use IOP instead	No	Orbix 3.0
IDL compiler options <code>-i</code> and <code>-f</code>		No	Orbix 3.0
IR	Replaced with the IFR	Yes	Orbix 3.0

Locator	Can implement own load balancing solution	Yes	Orbix 3.3
Non-native exceptions	Must use Native Exceptions	Yes	Orbix 3.3
TIE macro DEF_TIE(I,X)	Use other form	Yes	Orbix 3.3
Configuration Explorer (ConfigurationExplorer.bat)	Allows you to configure Orbix components without modifying the configuration files directly	No	Orbix 3.3 SP 5
Server Manager (ServerManager.bat)	Allows you to manage the Implementation Repository	No	Orbix 3.3 SP 5

Note: Orbix 3.0 was released February 1999 and Orbix 3.3 was released September 2000.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are cross platform unless otherwise stated. All bugs are described in terms of the following:

- Incident ID

This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.

- Synopsis

This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 11 C++ Edition:

Incident ID	Synopsis
ORBTHREE-573	Orbix 3.3.9 use of Getusername on vista causes Orbix to crash .
ORBTHREE-838	Orbix server crashes after installing Orbix3.3 SP10.
ORBTHREE-864	Sequence of sequence gives segmentation fault during code generation on Solaris.
ORBTHREE-934	Memory leak in Orbix server.

Orbix 3.3 SP 11 Java Edition

This section describes changes made to the Orbix 3.3 SP 10 Java Edition for the Orbix 3.3 SP 11 Java Edition.

New Features

Orbix 3.3 SP 11 Java Edition is binary compatible with Orbix 3.3 Java Edition. Orbix 3.3 SP 11 Java Edition now supports integration with Actional. This enables Orbix 3.3 applications and services to be monitored using Actional SOA management tools. Actional integration feature provides end-to-end visibility into the availability and performance of distributed Orbix applications. For more details, refer to the "Actional Integration with Orbix" guide for Orbix 3.3 SP11.

New and Modified APIs

Orbix 3.3 SP 11 Java Edition is binary compatible with Orbix 3.3 Java Edition. No new APIs were added, and no existing APIs were modified.

Functionality Removed

Orbix 3.3 SP 11 Java Edition is binary compatible with Orbix 3.3 Java Edition. No functionality is removed.

Deprecated Features

The following is a list of features deprecated in Orbix Java Edition:

Feature	Description	Feature Removed	When Deprecated
<code>_bind()</code>	Should use other means	No	OrbixWeb 3.2
Transformers	Can use SSL for security	No	OrbixWeb 3.2
Piggy backing data with filters	Should use Service Contexts	No	OrbixWeb 3.2
Opaque data type		No	OrbixWeb 3.2
Orbix network protocol (POOP)	Must use IIOp instead	No	OrbixWeb 3.2
IDL compiler options <code>-i</code> and <code>-f</code>		No	OrbixWeb 3.2
Orbix Java activator	Java activator in	No	Orbix 3.3 SP 5

(orbixdj.bat)	graphical mode		
---------------	----------------	--	--

Note: OrbixWeb 3.2 was released February 1999.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are cross platform unless otherwise stated. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 11 Java Edition:

Incident ID	Synopsis
ORBTHREE-525	The ClientConnection not cleaned up properly from ConnectionTable when the server process exits.
ORBTHREE-804	Race condition in unmarshalling any.

OrbixNames 3.3 SP 11

This section describes changes made to OrbixNames 3.3 SP 10 for OrbixNames 3.3 SP 11.

New Features

OrbixNames 3.3 SP 11 is binary compatible with OrbixNames 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Deprecated Features

The following is a list of features deprecated in OrbixNames:

Feature	Description	Feature Removed	When Deprecated
Names Service browser <code>NamesBrowser.bat</code>	Allow you to monitor and manage the Naming Service externally to your applications.	No	Orbix 3.3 SP 5

Bugs Fixed

No bugs were fixed in OrbixNames 3.3 SP 11.

Orbix Code Generation Toolkit 3.3 SP 11

This section describes changes made to the Orbix 3.3 SP 10 Code Generation Toolkit for the Orbix 3.3 SP 11 Code Generation Toolkit.

Note: The Orbix 3.0.1 and Orbix 3.3 Code Generation Toolkit Programmer's Guides state that there is IDLgen support for opaque data types. These statements are incorrect. IDLgen does NOT support opaque data types.

New Features

Orbix 3.3 SP 11 Code Generation Toolkit is binary compatible with Orbix 3.3. Code Generation Toolkit. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

Orbix Code Generation Toolkit 3.3 SP 11 is binary compatible with Orbix Code Generation Toolkit 3.3. No functionality is removed.

Bugs Fixed

No bugs were fixed in Orbix Code Generation Toolkit 3.3 SP 11.

Deprecated Features

Orbix Code Generation Toolkit component is deprecated in this release.

OrbixCOMet Desktop 3.3 SP 11

Orbix COMet Desktop component is no longer supported and is removed from this release.

Orbix Wonderwall 3.3 SP 11

This section describes changes made to Orbix Wonderwall 3.3 SP 10 for Orbix Wonderwall 3.3 SP 11.

New Features

Orbix Wonderwall 3.3 SP 11 is binary compatible with Orbix Wonderwall 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Deprecated Features

Orbix Wonderwall component is deprecated in this release:

Bugs Fixed

No bugs were fixed in Orbix Wonderwall 3.3 SP 11.

OrbixEvents 3.3 SP 11

This section describes changes made to OrbixEvents 3.3 SP 10 for OrbixEvents 3.3 SP 11.

New Features

OrbixEvents 3.3 SP 11 is binary compatible with OrbixEvents 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Deprecated Features

Orbix Events component is deprecated in this release.

Bugs Fixed

No bugs were fixed in OrbixEvents 3.3 SP 11.

Orbix SSL C++ 3.3 SP 11

This section describes changes made to OrbixSSL C++ 3.3 SP 10 for OrbixSSL C++ 3.3 SP 11.

New Features

OrbixSSL C++ 3.3 SP 11 is binary compatible with OrbixSSL C++ 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Credit Attribution

1. The bundled OpenSSL command line utility and toolkit includes software written by Eric A. Young (eay@cryptsoft.com). The version of OpenSSL used is 0.9.8i. The cryptographic libraries used by OrbixSSL C++ were also written by Eric A. Young. For more details on OpenSSL, please see the OpenSSL website at www.openssl.org.

Bugs Fixed

No bugs were fixed in Orbix SSL C++ 3.3 SP 11.

Known Problems

The installer does not automatically update the 64-bit SSL libraries with the default location of the Orbix SSL configuration file.

Orbix SSL Java 3.3 SP 11

This section describes changes made to OrbixSSL Java 3.3 SP 10 for OrbixSSL Java 3.3 SP 11.

New Features

OrbixSSL Java 3.3 SP 11 is binary compatible with OrbixSSL Java 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Deprecated Features

The following is a list of features deprecated in OrbixSSL Java 3.3 SP 11:

Feature	Description	Feature Removed	When Deprecated
RC2 Cipher Suite	JCP toolkit	Yes	Orbix 3.3
JPK File Support	JPK file support for loading private keys in OrbixSSL Java. <code>keyenc</code> utility stays for converting OrbixSSL private keys	No	Orbix 3.3.1

Bugs Fixed

There are no bug fixes in OrbixSSL Java 3.3 SP 11.

Credit Attribution

1. The bundled OpenSSL command line utility and toolkit includes software written by Eric A. Young (eay@cryptsoft.com). The version of openssl used is 0.9.8i. The cryptographic libraries used by OrbixSSL C++ were also written by Eric A. Young. For more details on OpenSSL please see the OpenSSL website at www.openssl.org.
2. OrbixSSL Java uses the JSSL/Jcrypto 2.0 toolkit as its backend SSL engine. The cryptographic libraries used by OrbixSSL Java were written by Baltimore Technologies.

OrbixOTS 3.3 SP 11

This section describes changes made to OrbixOTS 3.3 SP 10 for OrbixOTS 3.3 SP 11.

New Features

OrbixOTS 3.3 SP 11 is binary compatible with OrbixOTS 3.3. No new features are added and no existing features are modified.

New and Modified APIs

No new APIs are added and no existing APIs are modified.

Functionality Removed

No functionality is removed.

Deprecated Features

Orbix OTS component is deprecated in this release.

Bugs Fixed

No bugs were fixed in OrbixOTS 3.3 SP 11.

Appendix

This appendix contains information that is relevant to all versions of Orbix 3.3. It does not contain information that is relevant to only one version of Orbix 3.3. It contains information about performance tips, known problems and workarounds, enhancements and new features to Orbix 3.3, but not introduced in this version. It does not contain any information about bug fixes (please refer to previous release notes for these).

This appendix contains the following sections:

- Orbix C++ Edition
- Orbix Java Edition
- Orbix Code Generation Toolkit
- OrbixNames
- OrbixEvents
- OrbixSSL (C++ and Java)
- OrbixOTS

Orbix C++ Edition

This section describes changes made to Orbix Generation 3 C++ Edition products between Orbix 3.3 and Orbix 3.3 SP 10, which are relevant to Orbix 3.3 SP 11 C++ Edition.

New APIs

The following new APIs were added in Orbix 3.3 SP 9:

- `CORBA::BOA::getFileDescriptors(int*& fdSet)`
- `CORBA::ORB::getAllOrbixFDs(int*& fdSet)`
- `CORBA::ORB::getForeignFDSet(int*& fdSet)`
- `CORBA::ORB::getSelectableFDSet(int*& fdSet)`

For more details, see the *Orbix Reference Guide, C++ Edition*.

IFR Refactoring

Some refactoring of the IFR implementation was carried out in Orbix 3.3 SP 5 that affects repository storage. These changes affect the internal representation of the IFR repository. It is possible to continue using the existing IFR repository with the new IFR. However, if you start using the new IFR and need to revert back to the older versions (pre 3.3 SP 4) the IFR repository needs to be depopulated and repopulated using the original IDL files or a backup of the old repository. It is recommended that you back up your IFR repository before installing any service pack after Orbix 3.3 SP 5.

Tips

IT_MASK_SIGTERM, IT_MASK_SIGQUIT and IT_MASK_SIGINT

The `IT_MASK_SIGTERM`, `IT_MASK_SIGQUIT`, `IT_MASK_SIGINT` configuration variables are used to mask asynchronous signals (`SIGTERM`, `SIGQUIT`, `SIGINT`). While `IT_MASK_SIGUSR1` and `IT_MASK_SIGUSR2` are used to mask the user signals (`SIGUSR1`, `SIGUSR2`). In Orbix internal threads, do not use the `setConfigValue()` method to set these variables.

Before you start your application, you should export these variables as follows:

```
export IT_MASK_SIGTERM=YES
export IT_MASK_SIGQUIT=YES
export IT_MASK_SIGINT=YES
export IT_MASK_SIGUSR1=YES
export IT_MASK_SIGUSR2=YES
```

Known Problems

This section summarizes known issues and suggested workarounds for earlier Orbix 3.3 releases.

Incident ID	Synopsis
ORBTHREE-1	Orbix daemon memory leak.
64992	There is a known problem with foreign FDs (File Descriptors) on HPUX 11. When Orbix is asked to manage foreign FDs, there are some situations where the process hangs. It is not typical to ask Orbix to manage foreign FDs, and this problem can be avoided by not asking Orbix to manage foreign FDs.
64991	There is a known problem using C++ keywords in various situations in the IDL file. Using C++ keywords for attribute names, operations names and field names (of structures and exceptions) works. However, using C++ keywords as the type name of a module, interface, exception, or struct does not work. Customers should avoid using C++ keywords in the IDL as the type names of modules, interfaces, exceptions, and structs.
56121	The IDL compiler issues warnings if the IDL contains identifiers that are reserved keywords but not all lower case. For example, the IDL <code>interface Attribute{}</code> ; causes <code>Warning: identifier Attribute clashes with keyword</code> even though it is a valid interface name and is case-different from the reserved keyword <code>attribute</code> .
55600	No overloaded output-streaming operator (<<) is provided for the unsigned long long CORBA type (<code>CORBA::ULongLong</code>) in Orbix 3.3.
55599	No overloaded output-streaming operator (<<) is provided for the signed long long CORBA type (<code>CORBA::LongLong</code>) in Orbix 3.3.
55547	Orbix 3.3 generated IDL stub code on Windows NT for multi-dimensional arrays as in parameters should work around known VC6 multidimensional array const bug.
56334	When service context handlers in Orbix runtime encounter an abnormal condition, the diagnostic messages are not very informative.

Compilation problems on Windows NT result in the following error message:

Warning: Orbix wants an fd_set of size 1024 or greater. Please include CORBA.h before winsock2.h

This may be resolved by defining WIN32_LEAN_AND_MEAN when compiling. For example:

```
CL /c ... -DWIN32_LEAN_AND_MEAN ... myFile.cpp
```

If you do not wish to use this option when compiling you may also resolve the problem by editing CORBA.h by moving line 22,

```
#include <corba/PreCORBA.h>
```

to the position immediately after line 15,

```
#define CORBA_INCLUDES
```

Actional Integration

Usage of the Actional Integration feature in conjunction with a Thread Filter will result in the Actional Integration not reporting correctly when the ThreadFilter inRequestPreMarshal() method implementation returns -1. This is caused by the fact that the Actional Interceptor is implemented using Filters, and returning -1 from a ThreadFilter inRequestPreMarshal() method causes all subsequent Filters in the Filter not be invoked.

On HP-UX systems, the Actional Integration feature may fail to dynamically load within single-threaded processes.

The Actional Integration feature is implemented as a shared library that is dynamically loaded by the Orbix C++ runtime. This shared library links to a multi-threaded Actional C SDK library, used to communicate with the Actional Agent service. The HP-UX dynamic loader may fail to dynamically load this multi-threaded library within a single threaded process (that is, the orbix daemon).

In order to work around this issue, the LD_PRELOAD environment variable should be set so that the pthread library is preloaded.

To diagnose this issue and determine the location of the pthread library, perform the following:

HP-UX PA-RISC:

- Set the environment variable IT_SHLIB_VERBOSE to 1
- Execute your single-threaded process
- Look for the following line in the output:
 - /usr/lib/dld.sl: Can't shl_load() a library containing Thread Local Storage:
/usr/lib/libpthread.1

To resolve the issue, set LD_PRELOAD as mentioned below:

- LD_PRELOAD=/usr/lib/libpthread.1

HP-UX Itanium:

- Set the environment variable `IT_SHLIB_VERBOSE` to 1
- Execute your single-threaded process
- Look for the following line in the output:
 - `/usr/lib/hpux32/dld.so: Cannot dlopen load module '/usr/lib/hpux32/libpthread.so.1' because it contains thread specific data.`

To resolve the issue, set `LD_PRELOAD` as mentioned below:

- `LD_PRELOAD=/usr/lib/hpux32/libpthread.so.1`

Stopping double deletion of CORBA::Any when un-marshaling CORBA::Anys during DSI invocation processing

Some applications use the following pattern for memory management of CORBA::Anys required for DSI request processing. This is incorrect and causes a memory corruption error with this version of Orbix:

```
CORBA::NVList_ptr pArgList;
if (CORBA::Orbix.create_list(1, pArgList))
{
    CORBA::Short value_of_n = 0;
    // create an any on heap. This is the representative
    // of the in argument. All of the arguments (anys)
    // will be stored in an NV list
    //
    CORBA::Any* pAny = new CORBA::Any(CORBA::_tc_short,
        &value_of_n, 0);
    // populate the NV list with the heap allocated any
    // and name of "n"
    //
    pArgList->add_value("n", *pAny, CORBA::DSI_ARG_IN);
    // read all the arguments (values) from the request
    // into the NV list
    //
    rSrvReq.params(pArgList);
    // do invocation processing
    // ***** NOTE *****
    // Deleting the CORBA::Any is an error as the Orbix
    // runtime will do so.
    //
    delete pAny; // Error! Don't do this.
}
```

This code would not have caused problems prior to Orbix 3.3.1, because Orbix 3.3 and earlier versions did not properly delete the Any. Since Orbix 3.3.1, Orbix deletes the Anys, so it is no longer necessary to do it.

Deploying an Orbix 3.3 SP 9 daemon in Orbix 3.0.1 environment

An Orbix 3.3 SP 9 daemon can launch Orbix 3.0.1 servers. For all Orbix 3.0.1 daemon utilities, your clients and servers work with the Orbix 3.3 SP 9 daemon. You need to append the library path in the environment with the Orbix 3.3 SP 9 library path.

Note: This does not apply if you are using AIX 4.3.3 and 4.3.2 because none of the Orbix binaries built on AIX 4.3.3 operate on 4.3.2 daemon utilities.

Orbix Java Edition

This section describes changes made to Orbix Generation 3 Java Edition products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to Orbix 3.3 SP 11 Java Edition.

New Features

Since Orbix 3.3 SP 9, a callback port can be specified through the following configuration variables:

- `OrbixWeb.IT_CALLBACK_PORT_BASE`
- `Orbix.Web.IT_CALLBACK_PORT_RANGE`

These configuration variables specify the first port to be assigned, and the number of ports starting at this port number to assign. For example, a base of 5000 and range of 2 allocates 5000 and 5001 for the callbacks. If another client tries to connect with base and range after these two ports are assigned, an exception about setting the range to a larger size is thrown, and the client quits.

These configuration variables can be specified in any of the following ways:

- In the configuration file (`OrbixWeb3.cfg`).
- Programmatically through the code. For example:

```
IE.Iona.OrbixWeb._CORBA.Orbix.SetConfigItem("OrbixWeb.IT_CALLBACK_PORT_BASE", "5000");
IE.Iona.OrbixWeb._CORBA.Orbix.SetConfigItem("OrbixWeb.IT_CALLBACK_PORT_RANGE", "10");
```
- By passing them as system properties to the JVM when running the client. For example:

```
-DorbixWeb.IT_CALLBACK_PORT_BASE=5000
-DorbixWeb.IT_CALLBACK_PORT_RANGE=10
```

Implemented APIs

The following APIs are implemented:

Class	<code>IE.Iona.OrbixWeb.CORBA.Any</code>
Method	<code>public void insert_fixed (java.math.BigDecimal d, org.omg.CORBA.TypeCode type)</code>
Description	Takes one <code>java.math.BigDecimal</code> value along with <code>TypeCode</code> information, which includes scale and digits information.

Class	<code>IE.Iona.OrbixWeb.CORBA.Any</code>
Method	<code>Public void insert_fixed (java.math.BigDecimal d)</code>
Description	Takes one <code>java.math.BigDecimal</code> value without any typecode information
Class	<code>IE.Iona.OrbixWeb.CORBA.Any</code>
Method	<code>Public java.math.BigDecimal extract_fixed() throws BAD_OPERATION</code>
Description	Extracts fixed type data from Any and return a <code>java.math.BigDecimal</code> value.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the `javac` compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with `javac`. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

CORBA fixed-point data type support

The CORBA fixed-point data type is fully supported in this edition. It is possible, in this edition, to use fixed type variables in arrays, structures, sequences, unions, and other user-defined data types.

Support for multiple profiled IORs

In Orbix 3.3.4, the client ORB iterates over a multi-profiled IOR until it is able to establish a connection to a server. It always starts at the first profile when connecting or reconnecting to a server.

This new feature enables interoperability with Orbix 2000 servers that use high availability features (these features are detailed in the Orbix 2000 2.0 installation guide).

Known Problems

This section summarizes known issues and suggested workarounds in earlier Orbix 3.3 Java editions.

Incident ID	Synopsis
65605	The Server Manager GUI does not update when a server is started and then stopped (affects Orbix 3.3.2 and upwards). This GUI is deprecated.
64957	Fragmentation error occurs on the client side if large chunk of data is sent in fragments from an ASP 5.x and higher server. The Fragments received from the ASP server are malformed. This is interoperability issue between ASP and Orbix Java 3.3 SP 5.

OrbixNames fails to launch automatically on Windows NT

If you register the Naming Service with spaces in its `bootclasspath` variable in one of the following files, the OrbixNames server fails to be automatically launched by the daemon.

```
<Orbix installation directory>\bin\registerns12.bat
```

(Automatic launch should occur when you run one of the utilities for OrbixNames—for example, `ls ns`—or when you run a client or server that tries to use the Naming Service.)

The following error appears in the window for the Orbix Java daemon (`orbixdj`):

```
Can't find class java.lang.NoClassDefFoundError.
```

Solution

If you find the directory name `Program Files` in these files, replace every occurrence with `progra~1`:

```
<Orbix installation directory>\bin\registerns12.bat
```

The above batch files are for registering the OrbixNames server with the daemon. If you have already registered the OrbixNames server, you can undo this and register it again as follows. (Ensure that the daemon is running first.)

To undo the registration:

```
rmit NS
registerns12
```

Multiple “font not found” messages starting JDK 1.3.1

When the Server Manager and Configuration Explorer are launched, you get multiple `font not found` messages. The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed:

```
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]  
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]  
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]
```

Workaround

1. Customize the `font.properties` file for each machine.
2. Install the `SUNIWof` font packages.

Orbix Code Generation Toolkit

This section describes changes made to Orbix Generation 3 Code Generation Toolkit products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to Orbix Code Generation Toolkit 3.3 SP 11.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the javac compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Known Problems

- The parser used by the IDLgen supports CORBA 2.3 specifications. You may therefore encounter problems when using identifiers that are recognized as keywords by the CORBA 2.3 specification (for example, `factory`).
- The file that produces the list of genies is renamed from `-list` to `list.tcl`. However, the command line argument that produces the list of genies is still `IDLgen -list`.
- The environment variable used by the IDLgen engine has changed to use `IT_IDLGEN_CONFIG_FILE` instead of `IDLGEN_CONFIG_FILE`.
- The Orbix Code Generation Toolkit 3.3 genies supplied do not work with previous released versions (3.0.2 or earlier) of the IDLgen product. The paths to any custom genies need to be placed into the `idlgen.cfg` file in the configuration directory.

OrbixNames

This section describes changes made to Orbix generation 3 Names products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to OrbixNames 3.3 SP 11.

Features

IT_NAMES_REP_CLEAN_CNT configuration variable added to orbixnames3.cfg

The `IT_NAMES_REP_CLEAN_CNT` configuration variable is added to `orbixnames3.cfg`. This variable is used to remove deleted contexts from the configuration repository.

The default value for the new variable is set to 100, which means that after deleting 100 contexts the naming repository is cleared.

In previous versions of Orbix 3.3, the naming repository was cleared every time a context was deleted, which slowed down the performance of the Naming Service.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the `javac` compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with `javac`. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Known Problems

Note: The bug IDs 4276129 and 4285197 refer to JDK bugs and are not assigned by IONA.

Bug ID: 4276129 in JDK1.3.1 - Multiple font not found messages starting jdk1.3.1

When the Naming Service is persistently launched, the Password dialog box is displayed at the same time as the missing font messages below:

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---%d-*-*p-*-sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---%d-*-*p-*-sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---%d-*-*p-*-sun-fontspecific]
```

The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed.

Workarounds

- Customize the `font.properties` file for each machine.
- Install the `SUNIWof` font packages.

Bug ID: 4285197 in JDK 1.3.1 - Xbootclasspath prevents loading custom JNI libs (from user dirs):

When the Naming Service is launched by semi-secure `orbixd`, `libkdmjj.so/libkdmjj.s1/kdmjj.dll` of SSL is used to supply `orbixd` with the Naming service password. The marker used to launch the Naming Service involves `-Xbootclasspath` argument to the Java interpreter.

As a result of this bug, `orbixd` cannot supply the password to the KDM as the `kdmjj` library cannot be loaded. This results in the Naming Service asking for user input for password when it is automatically launched.

Workarounds

Solaris: Copy the `.so` into `${JDKHOME}/jre/lib/sparc` (or set a symbolic name).

HPUX: Copy the `.s1` into `${JDKHOME}/jre/lib/PA_RISC` (or set a symbolic name).

Windows NT: Copy the `.dll` into `${JDKHOME}\jre\bin`.

`${JDKHOME}` points to the JRE directory used in `IT_JAVA_INTERPRETER` used in `common.cfg`. This is the intended behavior.

The remaining steps are relevant for Solaris, HP-UX and NT.

All system classes only look up shared libraries in `$JAVA_HOME/bin`. If you do need to load custom libraries for the system classes, there are two choices:

1. Install custom libraries into `$JAVA_HOME/bin`;

2. Set the property `sun.boot.library.path` to include the user library path. The syntax is:

```
java -Dsun.boot.library.path=$JAVA_HOME/bin:$CUSTOM/bin ...
```

When an SSL-enabled Names Server NS is run persistently or automatically launched by the Orbix Daemon, it listens on the port given by configuration variable `IT_SSL_IIOP_LISTEN_PORT` in `orbixnames3.cfg`.

Follow the steps below to automatically launch an SSL-enabled OrbixNames server by the Orbix daemon, and use the KDM utility to supply password to `orbixd`:

1. `orbixssl.cfg` should have the following entries and values for Naming Service:

```
IT_AUTHENTICATE_CLIENTS = "TRUE";
IT_SECURITY_POLICY = "SECURE";
IT_DAEMON_POLICY = "SEMI_SECURE_DAEMON";
IT_KDM_ENABLED = "TRUE";
```

2. `orbixnames.cfg` should have `IT_SSL_IIOP_LISTEN_PORT` defined.

3. Start `orbixd`.

4. `putit NS -j -jdk2 -- -Xbootclasspath:[... set of jars ...]`
`IE.Iona.OrbixWeb.CosNaming.NS -secure`

5. Start `kdm`

6. `putkdm NS kdm-password`

7. NS is the Implementation repository entry required for automatically launching the Naming Service.

8. Use the C++ utilities with the `-s` option.

Orbix Wonderwall

This section describes changes made to Orbix Generation 3 Wonderwall products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to Orbix Wonderwall 3.3 SP 11.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the javac compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Known Problems

This section summarizes known issues and suggested workarounds in earlier Orbix Wonderwall releases.

Incident ID	Synopsis
12000109	<p>The JRE used for the IORexplorer utility on an Orbix 3.3.4 installation is incompatible with Pentium4 processors. This applies to all other Wonderwall GUI tools.</p> <p>Because all GUIs shipped with Orbix 3.3 are deprecated, this will not be fixed, and is closed as a restriction.</p>
67886	<p>Failures occur when the <code>idl_demo_sslcli</code> and <code>idl_demo_sslsrv</code> demos in <code>/Wonderwall/OrbixSSL/</code> are run in <code>semisecure</code> mode on all Windows platforms.</p> <p>For the <code>idl_demo_sslcli</code> demonstration, after launching <code>iiproxy</code> and when the client is run it fails with the following exception:</p> <pre>Unexpected system exception 1 org.omg.CORBA.COMM_FAILURE: Communication failure no server at host : 10.2.5.125 minor code: 12080 completed: No</pre> <p>This is because an incorrect certificate was picked up</p>

by the client.

For the `idl_demo_sslsrv` demonstration, when the client tries to communicate with the server, the server throws the following exception:

```
org.omg.CORBA.NO_PERMISSION: No permission for
attempted op.
SSL handshakefailure. : MAC failed.
[alertLevel=FATAL,
alertDescription=BAD
_RECORD_MAC] minor code: 10139 completed: No
at
IE.Iona.OrbixWeb.SSL.SSLSocketConnection.completeH
andshake(SSLSocketConnection.java:363)
at
IE.Iona.OrbixWeb.CORBA.ClientConnection.run(Client
Connection.java:1196)
at java.lang.Thread.run(Thread.java:484)
```

This is because of incorrect certificate used by the server.

Workarounds:

For the `idl_demo_sslcli` demonstration, replace the following line [32]

```
public static String KEYFILE="server.pem";
public static String KEYFILE="server.jpk";
```

in the source of server (`javaserver1.java`)

For the `idl_demo_sslcli` demonstration, replace the following line [32]

```
public static String KEYFILE="client.pem";
```

with

```
public static String KEYFILE="client.jpk";
```

in the source of server (`javaserver1.java`)

OrbixEvents

This section describes changes made to Orbix Generation 3 Events products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to Orbix Events 3.3 SP 11.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the javac compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Known Problems

Multiple event channels, when joined, slow down the performance of an events consumer significantly.

Tips on Designing and Configuring your System

There are some steps you can take when designing and configuring your system for optimal throughput. These include:

Implementing efficient consumers

The quicker the consumer returns control to the event channel, the higher the rate of events the channel can supply.

Not overloading any individual OrbixEvents server

The optimal number of consumers depends on different issues including the event size, speed of the server host, speed of the consumer, and so on, and is best calculated by trial and error.

Increasing the event buffer sizes

Each event channel maintains internal buffers of events and stores events until the consumer can process them. If the consumers are consistently slower than the suppliers, internal buffers can eventually fill and the suppliers block trying to supply events to the event channel. The suppliers block because the `push()` operation attempts to add an event to an event buffer and cannot complete until an event is removed from the buffer. An event is removed from the buffer after it is supplied to all registered consumers. To avoid such blocking situations, increase the event buffer sizes by changing the following configuration variables:

Configuration Variable	Description
IT_MAX_RECV_KB	This is the queue of events to be pushed to consumers. This can never be set to 0.
IT_MAX_PEND_KB	The queue size for events received by incoming push from a push supplier. This can be set to 0.
IT_MAX_SEND_KB	A thread takes the pending messages and moves them to this queue prior to sending. In the loop back case sending is simply the transfer to the receive queue. This can be set to 0.

OrbixSSL (C++ and Java)

This section describes changes made to Orbix generation 3 SSL (C++ and Java) products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to OrbixSSL 3.3 SP 11 (C++ and Java).

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the javac compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Known Problems

Baltimore J/SSL toolkit does not support PKCS12 certificate generated by SSLEAY.

The methods `getIssuer()` and `getSubject()` on the `IT_X509Cert` class both return instances of the `IT_AVAList` class. The `IT_AVAList` class provides a method, `byte[] convert(IT_Format)`, that allows you to convert an `AVAList` to DER format. This `convert` method returns null in this release. All other methods on `IT_AVAList` work as before.

The *OrbixSSL Java Programmer's Guide* incorrectly states that you can set `IT_SSL_TRACEFILE` and `IT_SSL_TRACE_LEVEL` in the configuration file. They can only be set in the environment.

OrbixOTS

This section describes changes made to Orbix generation 3 OTS products between Orbix 3.3 and Orbix 3.3 SP 9 that are relevant to OrbixOTS 3.3 SP 11.

Tips

Using the IDLJ compiler with JDK 1.4.x

Since JDK 1.4.0, the javac compiler is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The default code generated by the IDLJ compiler contains import statements without a namespace or package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when using JDK 1.4, supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following Knowledge Base article (4797.953):

[Why my existing IDL does not compile while using JDK 1.4.x](#)

Synchronization objects in Java

When using Synchronization objects in Java a user must set the following two environment variables in `orbixots.cfg`:

```
OTS_INTEROP="TRUE"  
OTS_ALWAYS_RETURN_CONTEXT="TRUE"
```

The first environment variable sets the IIOP/Service Context interoperable mode. The second setting always returns a propagation context to a foreign context.

Known Problems

OTS 3.3.1 Certification

OTS 3.3.1 is not certified for Solaris 2.6 with Oracle 8.1.6 the Oracle ProC compiler utility core dumps during compilation.

Apparent purify errors indicate leakage

OrbixOTS 3.3 is comprehensively tested for memory leakage. An apparent leak is reported in thread-specific storage. This is not a true leak, but rather memory allocated per thread that is reused during the lifetime of the thread and is freed when the process exits. No memory growth occurs during the life of the program. This issue is evident on operations of the

`ThreadLocal<sometype>` template class.

Transient ports break recovery

Recoverable servers participating in a transaction should ensure that their object references include the daemon port rather than their transient port. This is important in the event that the recoverable server goes down and the coordinating server must attempt transaction recovery. The recoverable server can only be restarted by the coordinating server if the recoverable server's IOR contains the daemon port. Therefore, avoid calling `CORBA::ORB::useTransientPort` in recoverable servers.

TransactionFactory::recreate() not supported

`TransactionFactory::recreate()` is not supported in the current release of the Java server. There is currently no way to create an implicit association with an explicitly propagated transaction.

C++ Client and Java server interoperability

Pure C++ clients do not interoperate with Java servers in this release. For example, the C++ `simpleclient` program in the `gridcache` demonstration does not work with the Java `filesys` server. This is because a pure C++ client uses an optimized transaction factory to create its transactions in the understanding that it does not have to co-ordinate the transaction. Because the Java server also cannot co-ordinate, the transaction is rolled back. A simple workaround is to implement the client as an OrbixOTS server.

Server Hangs on NT when many clients run sequentially

An OrbixOTS client supports a callback object whose object key includes the client's PID, which is used in the absence of a server name. In the unusual scenario where a large number of clients are run sequentially against an OrbixOTS server on the same NT machine, the PID used in one client process may be reallocated by the operating system to a second client process very soon after the first has completed. This may cause the OrbixOTS server to hang. It maintains a cache of client callback objects, and this cache may not be updated quickly enough to reflect the PID's reallocation. A simple workaround is to implement the client as an OrbixOTS server.

OrbixOTS and OrbixSSL

OrbixOTS clients implement callback objects to help manage transactions, and hence may require an OrbixSSL invocation policy to be configured. See the OrbixSSL documentation for more information on configuring policies for clients that implement callback objects.

Java OrbixOTS and OrbixSSL

Due to a problem in Orbix with callbacks to SSL-enabled Java servers, recovery is not possible for Java OTS SSL servers.

Simple Java clients continue to work with SSL if they do not register resources with the transaction. Bi-directional IIOp provides a runtime workaround because it is not necessary to open a new connection for the callback. This does not work for recovery because there is not an existing connection.