
Orbix 3.3 Service Pack 7 Core Services

Release Notes

July 2005

Contents

Introduction	2
Orbix 3.3 SP 7 Core Services C++ Edition	5
Orbix 3.3 SP 7 Core Services Java Edition	8
OrbixNames 3.3 SP 7	10
Appendix	11

Introduction

Orbix 3.3 SP 7 Core Services is a service pack release of Orbix 3.3 on Red Hat Enterprise Linux 3 and Windows XP X64. It supports Orbix Java edition, Orbix C++ edition and OrbixNames. This document contains information about Orbix 3.3 SP 7, including build information, details of bugs that have been fixed in this release, known problems and workarounds, new features, tips, and deprecated features.

Orbix 3.3 SP 7 and Orbix 3.0.1

For details of the changes that took place between Orbix 3.0.1 and Orbix 3.3, see the Orbix 3.3 Release Notes at <http://www.iona.com/docs> under the heading Orbix Generation 3.

There have been no changes to the APIs since Orbix 3.3.

Migrating from an Earlier Version of Orbix

For information on migrating from an earlier version of Orbix to Orbix 3.3 SP 7, see the Migration Guide at: www.iona.com/products/MigrationGuide.pdf

Interoperability with Other IONA Products

The Java and C++ editions of Orbix 3.3 SP 7 have been tested with, and are interoperable with each other, except for those areas that are documented under known problems.

The Java and C++ editions of Orbix 3.3 SP 7 have also been tested with, and are interoperable with, the following Orbix products:

- Orbix 3.3 SP 6 C++ and Java editions.
- Orbix 3.3 SP 5 C++ and Java editions.
- Orbix 3.3.4 C++ and Java editions.
- Orbix 3.3.3 C++ and Java editions.
- Orbix 3.3.2 C++ and Java editions.
- Orbix 3.3.1 C++ and Java editions.
- Orbix 3.3 C++ and Java editions.
- Orbix E2A Application Server Platform 6.0 SP3 C++ and Java.
- Orbix Trader 1.2.1 Java edition (no C++ edition available).
- Orbacus 4.0.5.
- Orbix 3.0.1
- OrbixWeb 3.2

Licensing

- The IDL compilers, `idl` and `idlj`, are licensed.
- The Orbix daemon `orbixd` is licensed.

Deprecated Features Policy

When a feature is deprecated it means that:

- No support for this feature is given for the current version and for subsequent versions (that is, we do not explain how to use it and we do not fix any bugs in this feature).
- If you have not used this feature before, DO NOT start using it with this release.
- If you are already using this feature then you should remove it if at all possible.
- The feature may not be present in future versions of the product.

Documentation Errata

The following is a list of errors in the Orbix 3.3 documentation errors. If you find an error in the documentation please email docs-support@iona.com for prompt confirmation.

- The `CORBA::ORB::connectionTimeout()` is in milliseconds and not in seconds as stated in the *Orbix Programmer's Reference, C++ Edition*.

Development Environments

This table details the operating system versions and compiler versions, on which Orbix 3.3 SP 7 Core Services is built and certified.

Platform and O/S version	Built on	Certified on	C++ Compiler version	JDK version
Red Hat Enterprise Linux 3	Yes	Yes	g++ (GCC) 3.2.3	1.4.2
MS Windows XP X64 Version 2003 (Service Pack 1)	Yes	Yes	MS C/C++ Optimizing Compiler Version 14 (MS Platform SDK)	1.5.0

Note: You can build and run an Orbix 3.3 SP 7 Core Services application on the above platforms.

NOTES to all elements/services that use Java

The following subsections contain information that is relevant for all elements/services that use Java.

JRE not included

The Orbix 3.3 SP 7 installer does not include a Java Runtime Environment (JRE).

New environment variable

A new environment variable, `JAVA_P_FLAG`, has been introduced in Orbix 3.3 SP 7. The purpose of this flag is to accommodate Orbix 3.3 Java's ORB classes implementation to take precedence over Sun's, while running Orbix 3.3 Java applications using JDK 1.4.

The Orbix 3.3 SP 7 installer automatically sets the value of this variable based on the selected JDK version. It sets the variable to `/p` for JDK 1.4 and leaves it blank for other JDK versions.

Once Orbix 3.3 SP 7 is installed, this variable is available in the environment script, `setenv.sh`, so that it is set in the Orbix environment.

For more details, read the following Knowledge Base articles:

- [What is JAVA_P_FLAG for and how is it used in Orbix 3.](#)
- [Why my existing IDL does not compile while using JDK 1.4.x.](#)
- [Why am I getting org.omg.CORBA.NO_IMPLEMENT or org.omg.CORBA.NO_PERMISSION exception while using JDK 1.4.x?](#)

Orbix 3.3 SP 7 Core Services C++ Edition

This section describes changes made to the Orbix 3.3 SP 6 C++ edition for the Orbix 3.3 SP 7 C++ edition.

New Features

Orbix 3.3 SP 7 C++ edition is binary compatible with Orbix 3.3 C++ edition. No new features were added and no existing features were modified.

New and Modified APIs

Orbix 3.3 SP 7 C++ edition is binary compatible with Orbix 3.3 C++ edition. No new APIs were added and no existing APIs were modified.

Functionality Removed

Orbix 3.3 SP 7 C++ edition is binary compatible with Orbix 3.3 C++ edition. No functionality has been removed.

Deprecated Features

The following is a list of deprecated features in Orbix C++ edition:

Feature	Description	Feature Removed	When Deprecated
<code>_bind()</code>	Should use other means.	No	Orbix 3.0
Transformers	Can use SSL for security.	No	Orbix 3.0
Piggy Backing Data with Filters	Should use Service Contexts.	No	Orbix 3.0
Opaque Data Type		No	Orbix 3.0
Orbix Network Protocol (POOP)	Must use IIOP instead.	No	Orbix 3.0
IDL Compiler options <code>-i</code> and <code>-f</code>		No	Orbix 3.0
IR	Replaced with the IFR.	Yes	Orbix 3.0
Locator	Can implement own load balancing solution.	Yes	Orbix 3.3
Non Native Exceptions	Must use Native Exceptions	Yes	Orbix 3.3
TIE macro <code>DEF_TIE(I,X)</code>	Use other form	Yes	Orbix 3.3
Configuration Explorer ConfigurationExplorer.bat	Allows you to configure Orbix components without modifying the configuration	No	Orbix 3.3 SP 5

	files directly.		
Server Manager ServerManager.bat	Allows you to manage the Implementation Repository.	No	Orbix 3.3 SP 5

Note: Orbix 3.0 was released February 1999 and Orbix 3.3 was released September 2000.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 7 C++ edition:

Incident ID	Synopsis
69774	Added functionality to the Orbix daemon to pass on a signal mask for SIGHUP.
69531	InReplyPostMarshall called out of place.
69526	IFR cannot handle re-opened modules.
69519	Orbix runtime behavior when a client's IDL is mismatched from the server is a security hole.
69500	The <code>_get_interface()</code> call fails if the IDL interface name contains the '_' character.
69447	Setting <code>IT_LOCAL_DOMAIN</code> from a client can cause the Orbix runtime to try and resolve a completely invalid hostname.
69385	Orbix was hanging on exit.
69355	per-client-pid may not always guarantee unique servers for each client.
69155	Receiving of IIOPI.1 fragmented messages broken.
69151	Doing a copy of a struct that contains an any, which contains a struct that contains a sequence of octets, causes segmentation fault.
69069	'Any' copy constructor not working correctly when 'Any' contains an Exception type
69030	Orbix 3.3.6 deletes impreg entries when <code>IT_daemon::removeSharedMarker()</code> is called.
68997	Orbix 3.3.x client crashes calling <code>_non_existent</code> while connecting to Orbix 2.3.9 on the mainframe.

Orbix 3.3 SP 7 Core Services Release Notes

68973	Orbix 3.0.1 does not follow more than one location_forward per object reference.
68948	Naming Service unavailable after 52 servers have been started up.
68857	Loss of performance in Orbix 3.3.6 due to new locks on multi-CPU machines.
68805	Fixed CORBA compliance issue with regard to IDL sequence type.
68463	Problem with the IDL compiler <code>-no_underscore</code> flag.
68357	Orbix Daemon Core Dump when running with <code>-a -t</code> option.
68336	Orbix on HP-UX is compiled with PSTAT64 enabled. This flag makes HP <code>proc_*</code> () system calls 64-bit compliant.
68330	Orbix 2.3.4 performs better than Orbix 3.3.6. when dealing with Anys. If the any contains a sequence and the sequence embeds a union data type, Orbix 3.3.6 is 20 times slower than 2.3.4 and Orbix 3.0.1.
68305	HP Patch PHNE 28538 has changed the behavior of the <code>read()</code> for non-blockingconnects. With that patch, <code>read()</code> will return <code>ECONNRESET</code> instead of <code>ECONNREFUSED</code> .
68271	<code>_non_existent</code> calls do not honour timeout specified in environment that is passed to it.
68269	Orbix 3.3 does not stop listening once <code>AtOrbixFDLowLimit</code> has been reached.
68255/68289	Response for Locate Request (<code>_start_server</code>) has changed in Orbix 3.3 C++ daemon, affecting communication with wonderwall.
68221	Orbix 3.3.5 allows null strings defined as out parameters to be sent back to clients.
68166	Enhancement request to add configuration to specify to Orbix 3.3 what port number to use for <code>ControlSocket</code> .
68028	Installing daemon as an NT service and trying to run from Control Panel results in "Microsoft Management Console" error.
67862	Orbix 3.3.4 hanging when selecting a new leader.

Orbix 3.3 SP 7 Core Services Java Edition

This section describes changes made to the Orbix 3.3 SP 6 Java edition for the Orbix 3.3 SP 7 Java edition.

New Features

Orbix 3.3 SP 7 Java edition is binary compatible with Orbix 3.3 Java edition. No new features were added and no existing features were modified.

New and Modified APIs

Orbix 3.3 SP 7 Java edition is binary compatible with Orbix 3.3 Java edition. No new APIs were added and no existing APIs were modified.

New Configuration Variable

A new OrbixWeb scoped configuration variable, `IT_CONNECT_ATTEMPTS`, has been added to Orbix Java edition. Users can modify it to set any value from 1. The default value for `IT_CONNECT_ATTEMPTS` is 5. However, the value set to this configuration variable will be ignored if your application is using `maxConnectRetries()` to set the maximum number of times the connection retries.

Functionality Removed

Orbix 3.3 SP 7 Java edition is binary compatible with Orbix 3.3 Java edition. No functionality has been removed.

Deprecated Features

The following is a list of features deprecated in Orbix Java edition:

Feature	Description	Feature Removed	When Deprecated
<code>_bind()</code>	Should use other means.	No	OrbixWeb 3.2
Transformers	Can use SSL for security.	No	OrbixWeb 3.2
Piggy Backing Data with Filters	Should use Service Contexts.	No	OrbixWeb 3.2
Opaque Data Type		No	OrbixWeb 3.2
Orbix Network Protocol (POOP)	Must use IIOP instead.	No	OrbixWeb 3.2
IDL Compiler options <code>-i</code> and <code>-f</code>		No	OrbixWeb 3.2

Orbix Java Activator (Orbixdj.bat)	Java Activator in Graphical mode	No	Orbix 3.3 SP 5
---------------------------------------	----------------------------------	----	----------------

Note: OrbixWeb 3.2 was released February 1999.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 7 Java edition:

Incident ID	Synopsis
69335	Can't activate two objects with different types using the same marker in an OrbixWeb server.
69331	The ORB's behaviour when determining if a call is collocated or not is inconsistent with the actual location of the target object.
69328	There's a 2 to 4 second delay for an OrbixWeb client to connect to the host/port in a reference when the server isn't actually running.
69108	OrbixWeb logging enhancements for additions to the diagnostic level of 1.
69107	Reference count problems cause the ConnectTable data structures to get filled with dead ClientConnection objects.
68922	Orbix 3.3.x Java server finds a deadlock scenario (hangs) when it is shutdown gracefully through deactivateImpl.
68823	One-way call fails from Orbix 3.3.5 Java client if no other call has been made before.
68662	MAX_CONNECT_ATTEMPTS not picked up by OrbixWeb. OrbixWeb.IT_CONNECT_ATTEMPTS is now stored in the OrbConfig class where it is accessible to the ORB class. It can be set from configuration file or command line.
68574	While marshalling strings, CDRcoder writeStringBuf() method is throwing ArrayIndexOutOfBoundsException when the number of bytes in the marshalling buffer is equal to the buffer size.
68237	Connection layer has been refactored.

Note: A new switch -jNoDeprecated is introduced to idlj compiler.

When this is used, idlj compiler does not generate java deprecated API calls in the skeleton and stub code. By default the value of this switch is **false**.

OrbixNames 3.3 SP 7

This section describes changes made to OrbixNames 3.3 SP 6 for OrbixNames 3.3 SP 7.

New Features

OrbixNames 3.3 SP 7 is binary compatible with OrbixNames 3.3. No new features have been added and no existing features have been modified.

New and Modified APIs

OrbixNames 3.3 SP 7 is binary compatible with OrbixNames 3.3. No new APIs have been added and no existing APIs have been modified.

Functionality Removed

OrbixNames 3.3 SP 7 is binary compatible with OrbixNames 3.3. No functionality has been removed.

Deprecated Features

The following is a list of features deprecated in OrbixNames:

Feature	Description	Feature Removed	When Deprecated
Names Service browser <code>NamesBrowser.bat</code>	Allow you to monitor and manage the Naming Service externally to your applications.	No	Orbix 3.3 SP 5

Bugs Fixed

The following bug was fixed in OrbixNames 3.3 SP 7:

Incident ID	Synopsis
69515	Major performance degradation in Naming Service between Orbix 3.3.6 and Orbix 3.3.7 TP5 on Solaris 8.

Appendix

This appendix contains information that is relevant to all versions of Orbix 3.3. It does not contain information that is relevant to only one version of Orbix 3.3. It contains information about performance tips, known problems and workarounds, enhancements and new features to Orbix 3.3, but not introduced in this version. It does not contain any information about bug fixes (please refer to previous release notes for these).

This appendix contains the following sections:

- Orbix C++ Edition
- Orbix Java Edition
- OrbixNames

Orbix C++ Edition

This section describes changes made to Orbix generation 3 C++ edition products between Orbix 3.3 and Orbix 3.3 SP 6, which are relevant to Orbix 3.3 SP 7 C++ edition.

IFR Refactoring

Some refactoring of the IFR implementation was carried out in Orbix 3.3 SP 5 that affects repository storage. These changes affect the internal representation of the IFR repository. With new IFR it is possible to continue using the existing IFR repository, however, if you start using the new IFR and need to revert back to the older versions (that is pre 3.3 SP 4) the IFR repository needs to be depopulated up and repopulated using the original IDL files or a backup of the old repository. IONA recommended that you backup your IFR repository before installing any service pack after Orbix 3.3 SP 5.

Tips

Use of IT_MASK_SIGTERM, IT_MASK_SIGQUIT and IT_MASK_SIGINT

In regard to the use of configuration variables IT_MASK_SIGTERM, IT_MASK_SIGQUIT, IT_MASK_SIGINT to mask the asynchronous signals (SIGTERM, SIGQUIT, SIGINT) and IT_MASK_SIGUSR1, IT_MASK_SIGUSR2 to mask the user signals (SIGUSR1, SIGUSR2) in Orbix internal threads, do not use the method `setConfigValue()` to set these variables.

You need to export these variables as follows before you start your application:

```
export IT_MASK_SIGTERM=YES
export IT_MASK_SIGQUIT=YES
export IT_MASK_SIGINT=YES
export IT_MASK_SIGUSR1=YES
export IT_MASK_SIGUSR2=YES
```

Known Problems

This section summarizes known issues and suggested workarounds for earlier Orbix 3.3 releases.

Incident ID	Synopsis
64992	There is a known problem with foreign FDs (File Descriptors) on HPUX 11. When Orbix is asked to manage foreign FDs, there are some situations where the process hangs. It is not typical to ask Orbix to manage foreign FDs, and this problem can be avoided by not asking Orbix to manage foreign FDs.
64991	There is a known problem using C++ keywords in various situations in the IDL file. Using C++ keywords for attribute names, operations names and field names (of structures and exceptions) works. However, using

	C++ keywords as the type name of a module, interface, exception, or struct does not work. Customers should avoid using C++ keywords in the IDL as the type names of modules, interfaces, exceptions, and structs.
56121	The IDL compiler issues warnings if the IDL contains identifiers that are reserved keywords but not all lower case. For example, the IDL "interface Attribute{};" causes the warning "Warning : identifier Attribute clashes with keyword" even though its a valid interface name and is case-different from the reserved keyword "attribute".
55600	No overloaded output-streaming operator (<<) is provided for the unsigned long long CORBA type (CORBA::ULongLong) in Orbix 3.3.
55599	No overloaded output-streaming operator (<<) is provided for the signed long long CORBA type (CORBA::LongLong) in Orbix 3.3.
55547	Orbix 3.3 generated IDL stub code on Windows NT for multi-dimensional arrays as in parameters should work around known VC6 multidimensional array const bug.
56334	When service context handlers in Orbix runtime encounter an abnormal condition, the diagnostic messages are not very informative.

Compilation problems on Windows NT result in the following error message:

"Warning: Orbix wants an fd_set of size 1024 or greater. Please include CORBA.h before winsock2.h"

This may be resolved by defining WIN32_LEAN_AND_MEAN when compiling.

For example: CL /c ... -DWIN32_LEAN_AND_MEAN ... myFile.cpp

If you do not wish to use this option when compiling you may also resolve the problem by editing CORBA.h by moving line 22,

```
#include <corba/PreCORBA.h>
```

to the position immediately after line 15,

```
#define CORBA_INCLUDES
```

Stopping double deletion of CORBA::Any when un-marshaling CORBA::Anys during DSI invocation processing.

Some applications use the following pattern for memory management of CORBA::Anys required for DSI request processing. This is incorrect and causes a memory corruption error with this version of Orbix:

```
CORBA::NVList_ptr pArgList;
if (CORBA::Orbix.create_list(1, pArgList))
{
    CORBA::Short value_of_n = 0;
    // create an any on heap. This is the representative
    // of the in argument. All of the arguments (anys)
    // will be stored in an NV list
    //
    CORBA::Any* pAny = new CORBA::Any(CORBA::_tc_short,
        &value_of_n, 0);
    // populate the NV list with the heap allocated any
```

```
// and name of "n"
//
pArgList->add_value("n", *pany, CORBA::DSI_ARG_IN);
// read all the arguments (values) from the request
// into the NV list
//
rSrvReq.params(pArgList);
// do invocation processing
// ***** NOTE *****
// Deleting the CORBA:Any is an error as the Orbix
// runtime will do so.
//
delete pAny; // Error! Don't do this.
}
```

This code would not have caused problems prior to Orbix 3.3.1 as Orbix 3.3 and earlier versions did not properly delete the `Any`. Since Orbix 3.3.1, Orbix deletes the `Anys`, so it is no longer necessary to do it.

Deploying an Orbix 3.3 SP 7 Daemon in Orbix 3.0.1 Environment

An Orbix 3.3 SP 7 daemon can launch Orbix 3.0.1 servers. For all Orbix 3.0.1 daemon utilities, your clients and servers work with the Orbix 3.3 SP 7 daemon. All you need to do is append the Library Path in the environment with the Orbix 3.3 SP 7 library path.

Orbix Java Edition

This section describes changes made to Orbix generation three Java edition products between Orbix 3.3 and Orbix 3.3 SP 6 that are relevant to Orbix 3.3 SP 7 Java edition.

Implemented APIs

The following APIs have been implemented:

Class	IE.Iona.OrbixWeb.CORBA.Any
Method	public void insert_fixed (java.math.BigDecimal d, org.omg.CORBA.TypeCode type)
Description	Takes one <code>java.math.BigDecimal</code> value along with <code>TypeCode</code> information, which includes scale and digits, information.
Class	IE.Iona.OrbixWeb.CORBA.Any
Method	Public void insert_fixed (java.math.BigDecimal d)
Description	Takes one <code>java.math.BigDecimal</code> value without any typecode information
Class	IE.Iona.OrbixWeb.CORBA.Any
Method	Public java.math.BigDecimal extract_fixed() throws BAD_OPERATION
Description	Extracts fixed type data from Any and return a <code>java.math.BigDecimal</code> value.

Tips

Using the IDLJ compiler with JDK 1.4.x

The `javac` compiler, since JDK 1.4.0, is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The code generated by default by the IDLJ compiler contains import statements without a namespace or a package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with `javac`. Therefore, when you are using JDK 1.4, you need to supply `-jP <packagename>` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following IONA Knowledge Base article:

[Why my existing IDL does not compile while using JDK 1.4.x.](#)

CORBA Fixed-Point Data Type Support

The CORBA fixed-point data type is fully supported in this edition. It is possible, in this edition, to use fixed type variables in arrays, structures, sequences, unions, and other

user-defined data types.

Support for Multiple Profiled IORs

In Orbix 3.3.4 the Client ORB iterates over a multi-profiled IOR until it is able to establish a connection to a server. It always starts at the first profile when connecting or reconnecting to a server.

This new feature enables interoperability with Orbix 2000 servers that utilize high availability features (these features are detailed in the Orbix 2000 2.0 install guide).

Known Problems

This section summarizes known issues and suggested workarounds in earlier Orbix 3.3 Java edition.

Incident ID	Synopsis
65605	The Server Manager GUI doesn't update when a server is started and then stopped (affects Orbix 3.3.2 and upwards). This GUI is deprecated.
64957	Fragmentation error occurs on the client side if large chunk of data is sent in fragments from an ASP 5.x and higher server. The Fragments received from the ASP server are malformed. This is interoperability issue between ASP and Orbix Java 3.3 SP 5.

JVM 1.2.2-8/1.2.2_12 segmentation violations on Tru64 5.1A

There is a known problem on the Compaq Tru64 5.1A platform when running an Orbix 3.3 SP 7 Java application and using the 1.2.2-8 or 1.2.2-12 JDK. By default Just-in-Time (JIT) compilation is enabled and in some circumstances, this may cause a segmentation violation error to occur in the 1.2.2 Java interpreter. This results in the following output:

```
SIGSEGV 11* segmentation violation
si_signo [11]: SIGSEGV 11* segmentation violation
```

This behavior on Tru64 5.1A with JDK 1.2.2_8/12 has been confirmed by Compaq (Ref. No. "Java PTR #80-6-619") and is currently being investigated.

Workaround

Compaq recommend disabling of the JVM JIT compilation on the Tru64 5.1A platform. This can be done by setting the environment variable "JAVA_COMPILER" to "NONE" before running your application. You can verify that JIT compilation is not being used by checking the output of `java -version`:

```
$ export JAVA_COMPILER=NONE
$ java -version
java version "1.2.2-12"
Classic VM (build J2SDK.v.1.2.2:08/14/2001-17:00, native threads, nojit)
mailto:support@iona.com if you require any further information.
```

OrbixNames Fails to Launch Automatically on Windows NT

If you register the Naming Service with spaces in its `bootclasspath` variable in one of

the following files, the OrbixNames server fails to be automatically launched by the daemon.

```
<IONA installation directory>\bin\registerns12.bat
```

(Automatic launch should occur when you run one of the utilities for OrbixNames, `lsns` for example, or when you run a client or server that tries to use the Naming Service.)

An error like this appears in the window for the Orbix Java daemon (`orbixdj`):

```
Can't find class java.lang.NoClassDefFoundError.
```

Solution

If you find the directory name "Program Files" in these files, replace every occurrence with `progra~1`:

```
<IONA installation directory>\bin\registerns12.bat
```

The above batch files are for registering the OrbixNames server with the daemon. If you have already registered the OrbixNames server, you can undo this and register it again as follows. (Ensure that the daemon is running first of all.)

To undo the registration:

```
rmit NS
registerns12
```

Multiple "font not found" messages starting JDK 1.2.2 (and 1.3.1)

When Server Manager and Configuration Explorer are launched, you get multiple `font not found` messages. The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed:

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---*%d-*-*p-*-*sun-fontspecific]
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---*%d-*-*p-*-*sun-fontspecific]
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal---*%d-*-*p-*-*sun-fontspecific]
```

Workaround

1. Customize the `font.properties` file for each machine.
2. Install the `SUNIWof` font packages.

OrbixNames

This section describes changes made to Orbix generation three Names products between Orbix 3.3 and Orbix 3.3 SP 6 that are relevant to Orbix 3.3 SP 7 Names.

Features

IT_NAMES_REP_CLEAN_CNT Configuration Variable added to orbixnames3.cfg

The configuration variable, `IT_NAMES_REP_CLEAN_CNT`, has been added to `orbixnames3.cfg`. This variable is used to remove deleted contexts from the configuration repository.

The default value for the new variable is set to 100, which means that after deleting 100 contexts the naming repository is cleared.

In previous versions of Orbix 3.3 the naming repository was cleared every time a context was deleted which slowed down the performance of the Naming Service.

Tips

Using the IDLJ compiler with JDK 1.4.x

The `javac` compiler, since JDK 1.4.0, is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The code generated by default by the IDLJ compiler contains import statements without a namespace or a package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with `javac`. Therefore, when you are using JDK 1.4, you need to supply `"-jP <packagename>"` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following IONA Knowledge Base article:

[Why my existing IDL does not compile while using JDK 1.4.x.](#)

Known Problems

Note: The bug IDs 4276129, and 4285197 refer to JDK bugs, and are not assigned by IONA.

Bug ID: 4276129 in JDK 1.2.2 - Multiple font not found messages starting jdk1.2.2

When the Naming Service is persistently launched, the Password dialog box is displayed at the same time as the missing font messages below:

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-
```

```
r-normal--*-%d-*-*p-*-*sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-  
r-normal--*-%d-*-*p-*-*sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-  
r-normal--*-%d-*-*p-*-*sun-fontspecific]
```

The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed.

Workarounds

- Customize the `font.properties` file for each machine.
- Install the SUNIWoF font packages.